

**Standalone Door Controller**  
PR-8910 / PR-8913

MODEL	PR-8910	PR-8913	PR-8915
Reading Mode	EM card	RF ID	EM card/ 120KHZ
Reading Distance	5~15cm	5~15cm	6.5cm
Sensing Time		<0.1s	
Card Capacity	800 cards	2000 ID Cards	1000 cards
Door-Open Mode		Password, card, card + password	4 D, 4D+C, C+C, 4D+4D
Working voltage	DC 9~15V	12V DC	12V DC
Unlock current	<1000mA	<0.1A	<130mA
Static current	<60mA	<400mA	<400mA
Operating Temp	-10°C +55°C	-20C~+60	-31°C ~ +63°C
Working humidity		0%~90%	
Product size	117x117x21mm	86x86x20mm	120x76x27mm
Color	Grey	Metalic	Metalic
Material	Plastic	Steel/ Plastic	Steel
Water proofing	Nil	Yes	IP-67
Weight	200g	0.15KG	410g
Backlights	Nil	Yes	LED Blue&Black

Buzzer Built-in Door bell controller & buzzer

**APPLICATION**

Intelligent building, small size offices, Government offices, R&D institutes, Business buildings, Telecommunication base stations, non-attendance bank, Intelligent residential areas, Homes, Financial organizations, Equipment rooms, Storage for valuable items

**Standalone Mini Door Controller**  
PR-320/ PR-322

MODEL	PR-320	PR-322	PR-324
Door Open Mode	Password(8 Sets),Proximity	Password	Password
User Capacity	2000 Cards/6 Digit(8sets)	1200 Groups/6 Digit Password	1000 Password
LED Indicator	LED rectangle	Red/Green Toggle	Yes
Admin Password		1 Group	
Working Voltage	DC 12V	DC 10~15V	12V~24V AC/DC
Unlock Current		< 1000 m A	15~100mA
Static Current		< 50 m A	<50mA
Structure	Standard Rectangle Box	Standard 86 Box	Standard Steel Box
Operating Temp	0~65°C	-10°C ~ 55°C	-20°C ~ 60°C
Operating Humidity	0~85%RH	0~90% RH	0~95% RH
Size	12.5x3.3x7	95*95*24 mm	117*72*40 mm

**Vandal Resistant Access Control**

**FEATURE**

Reads password and/or 125KHz EM card; Customizable to read 13.56MHz Mifare card  
Anti-vandal, Waterproof & Back-lit Metal Key Buttons  
Audible beep and visible indicator provide feedback for the user  
Access control interfaces for electric lock, door sensor, alarm, exit button and doorbell  
Lock control delay, Unlock duration, Alarm delay are programmable from 0 to 255 second, Tamper alarm, door sensor alarm, error operation alarm.

MODEL	PR-8919	Access Control Interface	Electric Lock,Door Sensor,
LED Indicator	Green, Red		Alarm, Exit button and Door bell
Keypad	White backlit, Numeric Keys 0~9, Function keys *, #, Bell	Power	DC 12V
Verification type	Card , PW, Card/PW, Card+P/W	Operating Temperature	-20 C ~ 50C
Built-in Card Reader	EM Card (optional Mifare card)	Operating Humidity	<95%
Card Capacity	999	Dimensions	52x118x24mm
Password Capacity	8 Password Groups	IP Rating	IP66



PR-8910 / PR-8913



PR-8915



PR-322



PR-320

**SELECTION**

PR-320 Password, Proximity Card  
PR-322 Password Reader  
PR-324 Password Reader



PR-8919



MODEL	PR-8920	PR-8921	PR-8930	PR-8931
Reading Mode	EM / EM compatible card	Mifare card	EM / EM compatible card	Mifare card
LCD Display	---	---	2-line UK English	2-line UK English
Reading Distance	5~15cm	2~10cm	5~15cm	2~15cm
Sensing Time		< 0.1s		
Card Capacity		3500 cards		
Off-line Record		2000		
Communication Mode			RS-232/485, TCP/IP (converter)	
Network distance		1200m / RS485	15m / RS232, 1200m / RS485,	1200m / RS485
			100m / direct TCP/IP	
Transmission Rate		4800, 9600 bps		
Door-open Mode		Password, Card, Card + Password		
Working Voltage		DC9 ~ 15V		
Unlock current		<1000mA		
Static current		<60mA		
Operating Temp		-10°C ~ 55°C		
Working Humidity		0% ~ 90%		
Product size		150x88x25mm		
Color	Grey		Black	

**Intelligent Access Reader without Keypad**  
PR-2600 Series



MODEL	PR-2610	PR-2615	PR-2610N	PR-2615N
Reading Range	5 ~15 cm	up to 5 cm	Up to 10 cm	Up to 5 cm
Reading Time & Card	EM Card <10ms/ byte	13.56Mhz Mifare Card <300ms		<300ms
Power / Current	DC 12~15V/ 80~90mA	DC 6~14V/ 70mA Max		DC 6 ~ 14V / Max 7.0mA
Input Port		2ea(External LED contro I, External Buzzer Control)		
Output Format		26 bit wiegand (Default)		34 bit wiegand(Default)
LED Indicator	Red	2 Color LED indicators (Red and Green)		2 Color LED indicators (Red and Green)
Beeper		---		Yes
Operating Temperature	-15C ~ 65C	-20 C ~ 65C		-20 C ~ 65 C
Operating Humidity		0~90%		10% ~90% RH (non condensing)
Color		---		Black
Material		---		ABS+PC with Texture
Size	100x70x22mm	116x75x17.3mm		86x86x16mm
IP Rating		IP 65		