

MODEL	KV-4B	KV-4C	KRC-50
Working Voltage	AC 110/240V		
Working Current	<600A B/W	<400A Color	
Wiring	4 Wires	5 Wires	
Communication duration	60~90 sec	---	
Ambient Humidity	45% ~ 95%		
Ambient temperature	+55C ~ -12C		
Video output	15625 Hz 1.0Vp~p 75ohm, PAL /		
Product dimension	NTSC	190x210x60	
Protection level	190x215x70mm	mm	
Net weight	IP54	1.22kg	1.22kg



**Video Doorphone with Handset  
KV-50 (5" / 5.6")**



MODEL	KV-50
Ambient Humidity	AC 110/240V
Working Current Static	B/W <600mA / Color <400mA
Wiring	4 Wires
Communication duration	45~90 sec
Ambient Humidity	45% ~ 95%
Ambient temperature	+55C ~ -12C
Video output	15625 Hz 1.0Vp~p 75ohm, PAL /
Product dimension	NTSC
Inner package	284x225x60mm
Protection level	290x234x80mm
Net weight	IP54

**Video Doorphone Monitor  
KV-202C (4" / 5.6")**

MODEL	KV-202C
Ambient Humidity	AC 110/240V
Working Current Static	Static <200mA Dynamic < 650mA
Wiring	4 Wires
Communication duration	60~90 sec
Ambient Humidity	45% ~ 95%
Ambient temperature	+55C ~ -12C
Video output	15625 Hz 1.0Vp~p 75ohm, PAL /
Product dimension	NTSC
Inner package	252x182x40mm
Protection level	256x242x56mm
Net weight	IP54



**Video Doorphone Monitor  
KV-50A / KV-102C**

MODEL	KV-50A / KV-102C
Working Voltage	AC 110/240V
Working Current	B/W <600mA / Color <400mA
Wiring	4 Wires
Communication duration	45~90 sec
Ambient Humidity	45% ~ 95%
Ambient temperature	+55C ~ -12C
Video output	15625 Hz 1.0Vp~p 75ohm, PAL / NTSC
Protection level	IP54
Net weight	1.20kg



ITEM	Dimension
KDV-50A	280x140x55mm
KDV-102C	218.5x191x54mm

**High Resolution Door Phone Camera  
KV-4BP / KV-4CP / KV-67C**

MODEL	KV-4BP	KV-4CP
Ambient Humidity	45% ~ 95%	
Ambient Temperature	+75°C ~ 40°C	
Working current	230 +20mA	
Resolution	480 TVL CCD sensor	
Video Output	1.0Vp~p 75ohm , PAL / NTSC	
Wiring	4 wires	
Product dimension	120x42.5x40mm	
Inner package	190x112x54mm	
Protection level	IP54	
Net weight	1.3 kg	
Grass weight	0.27 kg	



MODEL	KV-4BPB	KV-4CPB
Ambient Humidity	45% ~ 95%	
Ambient Temperature	+75°C ~ 40°C	
Working current	230 +20mA	
Resolution	480 TVL CCD sensor	
Video Output	1.0Vp~p 75ohm , PAL / NTSC	
Wiring	4 wires	
Product dimension	198x125x63mm	
Inner package	200x130x74mm	
Protection level	IP54	
Net weight	0.35 kg	
Grass weight	0.45 kg	

**High Resolution Door Phone Camera  
KV-4BPB / KV-4CPB / KV-68V**



**High Resolution Door Phone Camera  
KV-4BANS / KV-4CANS**



MODEL	KV-4BANS	KV-4CANS
Ambient Humidity	45% ~ 95%	
Ambient Temperature	+75°C ~ 40°C	
Working current	CMOS 100 +1-mA / CCD 150 +20mA	
Resolution	480 TVL CCD Sensor	
Video Output	1.0Vp~p 75ohm , PAL / NTSC	
Wiring	4 wires	
Product dimension	185x123x62mm	
Inner package	238x130x80mm	
Protection level	IP54	
Net weight	0.64 kg	
Grass weight	0.73 kg	

**High Resolution Door Phone Camera  
KDP-201R / KD-1A**



MODEL	KDP-201R / KD-1A
Ambient Humidity	45% ~ 95%
Ambient Temperature	+75°C ~ 40°C
Wiring	Two wires
Product dimension	125x105x45mm
Inner package	200x128x45mm
Protection level	IP54
Net weight	1.16 kg