



PR-AHD 7116 D

Features

H.264 Video Compression
G.711a Audio Compression
Gigabit Ethernet Interface
2 USB ports for Backup
2 SATA (Optional)
3G, WIFI(expand via USB)
Power 12V/4A

Merits

Cloud storage & VMS Support
Mobile application support
P2P Connectivity
Quick Setup for Recording
Emergency recording & Backup
Networking bandwidth control
CMS & Network viewer integration

Applications

Shopping Malls
Hospitals
Hotels
Military & Police installations
Corporate & enterprise level
Factories
Large warehouses

SPECIFICATIONS

Model	PR-AHD 7116 D
Video codec	H.264
Encode	16*AHD-H@15fps
Decode	8*AHD-H@15fps
Multi-mode input	Analog:16*AHD-H ; 16*AHD-M; Mixed : 2*AHD-H(analog)+2*1080P (network) ; 4*AHD-M(analog)+4*720P (network); Network : 1*1080P+8*720P ; 4*1080P ;
Audio compression	G.711A
Intercom	support
Record mode	Manual>alarm>motion detection>timing
Playback Channels	8 (pure local input mode)
Space occupation	960H : 12~20G/ day*channel 720P : ~20G/ day*channel 1080P 20~30G/ day*channel audio : 691.2M/ day*channel
Backup mode	Network backup、 USB HDD、 USB writer、 SATA writer
Video inout	16 BNC
Video output	1ch VGA,1ch HDMI
Audio input	4ch RCA
Audio output	1ch RCA
Alarm input	8
Alarm output	1
Network interface	RJ45 10M/100M /1000M Adaptive Ethernet port
PTZ control	RS485; RS232; support multiple PTZ protocols
USB	2 USB ports
Hard disk	2 SATA (Each maximum support 6T)
Wireless	3G、 WIFI(expand via USB)
Power	12V/4A
Dimension	350mm(length)* 296mm(width)* 44mm(height)

Features

H.264 Video Compression
G.711a Audio Compression
Network backup, USB HDD,
Audio 16Ch In / 1Ch Out
Gigabit Ethernet Interface
2 USB ports for backup
4 & 8 SATA (Optional)
3G, WIFI (expand via USB)
Power DC 12V / 6A

Merits

Cloud storage & VMS Support
Mobile application support
P2P Connectivity
Quick Setup for Recording
Emergency recording & Backup
Networking bandwidth control
CMS & Network viewer integration

SPECIFICATIONS

Model	PR-AHD 7124 D	PR-AHD 7132 D
Video codec	H.264	H.264
Encode	24*AHD-M@15fps	32*AHD-M@15fps
Decode	24*AHD-M@15fps	8*AHD-M@15fps
Multi-mode input	"PureAnalog:24* AHD-M, 16*AHD-M ; 16*AHD-L; Mixed : 4*AHD-M(analog)+2*720P (network) ; Pure Network : 4*1080P, 1*1080P+8*720P, 20*960H ; "	"PureAnalog:32* AHD-M, 24*AHD-M, 16* AHD-M, 16*AHD-L; Mixed : 4*AHD-M(analog)+2*720P (network) ; Pure Network : 1*1080P+8*720P, 4*1080P, 20*960H ; "
Audio compression	G.711A	G.711A
Intercom	support	support
Record mode	Manual>alarm>motion detection>timing	Manual>alarm>motion detection>timing
Playback Channels	8 (pure local input mode)	8 (pure local input mode)
Space occupation	"960H : 12~20G/ day*channel 720P : ~20G/ day*channel 1080P 20~30G/ day*channel audio : 691.2M/ day*channel"	"960H : 12~20G/ day*channel 720P : ~20G/ day*channel 1080P 20~30G/ day*channel Audio : 691.2M/ day*channel"
Backup mode	Network backup、 USB HDD、 USB writer、 SATA writer	Network backup、 USB HDD、 USB writer、 SATA writer
Video inout	24 BNC	32 BNC
Video output	1ch VGA,1ch HDMI	1ch VGA,1ch HDMI
Audio input	16ch RCA	16ch RCA
Audio output	1ch RCA	1ch RCA
Alarm input	16	16
Alarm output	4	4
Network interface	RJ45 10M/100M /1000M Adaptive Ethernet port	RJ45 10M/100M /1000M Adaptive Ethernet port
PTZ control	RS485; RS232; support multiple PTZ protocols	RS485; RS232; support multiple PTZ protocols
USB	2 USB ports	2 USB ports
Hard disk	4/8 SATA (Each maximum support 6T)	4/8 SATA (Each maximum support 6T)
Wireless	3G、 WIFI(expand via USB)	3G、 WIFI(expand via USB)
Power	4SATA:12V/6A;8SATA:ATX power	4SATA:12V/6A;8SATA:ATX power
Dimension	259*148mm	259*148mm



PR-AHD 7132 D



PR-AHD 7124 D

Applications

Shopping Malls
Hospitals & Hotels
Military & Police installations
Corporate & enterprise level
Factories
Large warehouses